










































































Item No.	Picture	Dimension	English description	Unit price (USD)	
				CREE Chip	Epsistar chip
HB-15W			Dimension: 128mm*110mm*38mm Watts: 15W (5PCS*3W LED high power Epistar chip) Voltage: 10-30V DC Lumen: 1150LM CCT: 6000K Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing material: diecast aluminum Light distribution: focus30°/flood60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 11.2kg) Carton dimension: 320mm*290mm*290mm	/	\$11.79 (Epistar chip)
HB-18W			Dimension: 128mm*Φ116mm*40mm Watts: 18W (6PCS*3W LED high power Epistar chip) Voltage: 10-30V DC Lumen: 1250LM CCT: 6000K Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing material: diecast aluminum Light distribution: focus30°/flood60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 11kg) Carton dimension: 320mm*290mm*290mm	/	\$11.79 (Epistar chip)
HB-24W-A			Dimension: 128mm*Φ116mm*48mm Watts: 24W (8PCS*3W LED high power Epistar chip) Voltage: 10-30V DC Lumen: 1800LM CCT: 6000K Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing material: diecast aluminum Light distribution: focus30°/flood60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 10.8kg) Carton dimension: 350mm*320mm*260mm	/	\$12.95 (Epistar chip)
HB-24W-B			Dimension: 128mm*110mm*38mm Watts: 24W (8PCS*3W LED high power Epistar chip) Voltage: 10-30V DC Lumen: 1800LM CCT: 6000K Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing material: diecast aluminum Light distribution: focus30° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 11.2kg) Carton dimension: 350mm*290mm*290mm	/	\$12.95 (Epistar chip)
HB-27W-A			Dimension: 128mm*Φ116mm*65mm Watts: 27W (9PCS*3W LED high power Epistar chip) Voltage: 10-30V DC Lumen: 2200LM CCT: 6000K Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing material: diecast aluminum Light distribution: focus30° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 16kg) Carton dimension: 350mm*320mm*260mm	/	\$13.95 (Epistar chip)
HB-27W-B			Dimension: 128mm*Φ110mm*55mm Watts: 27W (9PCS*3W LED high power Epistar chip) Voltage: 10-30V DC Lumen: 2200LM CCT: 6000K Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing material: diecast aluminum Light distribution: focus30°/flood60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 16kg) Carton dimension: 350mm*320mm*260mm	/	\$13.95 (Epistar chip)
HB-30W			Dimension: 126mm*126mm*85mm Watts: 30pcs 1W high power LED Voltage: 10-30V DC Lumen: 2400LM CCT: 6500K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: diecast aluminum Light distribution: flood 160° Operating temperature: -40°C~80°C Package: 1pcs/package (12pcs/carton, gross weight: 22.5kg) Carton dimension: 440mm*370mm*350mm	/	\$49.69 (Epistar chip)
HB-40W			Dimension: 170mm*114mm*83mm Watts: 40W (4PCS*10W LED CREE chip) Voltage: 10-30V DC Lumen: 3200LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: diecast aluminum Light distribution: focus30° flood 60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (12pcs/carton, gross weight: 18.8kg) Carton dimension: 390mm*380mm*350mm	\$29.95 (CREE chip)	/



HB-42W			Dimension: 116mm*116mm*76mm Watts: 42W (14PCS*3W LED Epistar high power chip) Voltage: 10-30V DC Lumen: 3400lm Waterproof rate: IP67 Lens: PC CCT: 6500K Casing color: black Casing metrial: diecast aluminum Light distribution: focus30° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(20pcs/carton, gross weight: 21.7kg) Carton dimension: 500mm*360mm*320mm	/	\$22.95 (Epistar chip)
HB-48W-A			Dimension: 165mm*120mm*85mm Watts: 48W (16PCS*3W LED CREE chip) Voltage: 10-30V DC Lumen: 4000LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing metrial: diecast aluminum Light distribution: focus30° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(12pcs/carton, gross weight: 18.8kg) Carton dimension: 390mm*380mm*350mm	/	\$32.55 (Epistar chip)
HB-48W-B			Dimension: 110mm*110mm*72mm Watts: 48W (16PCS*3W LED Epistar high power chip) Voltage: 10-30V DC Lumen: 3200lm Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing metrial: diecast aluminum Light distribution: focus30° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(20pcs/carton, gross weight: 36kg) Carton dimension: 480mm*340mm*300mm	/	\$23.95 (Epistar chip)
HB-51W			Dimension: 160mm*160mm*86mm Watts: 51W (17PCS*3W LED Epistar high power chip) Voltage: 10-30V DC CCT: 6500K Lumen: 3700LM Waterproof rate: IP67 Lens: PMMA organic glass Casing color: black Casing metrial: diecast aluminum Light distribution: focus30° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(6pcs/carton, gross weight: 18.8kg) Carton dimension: 400mm*200mm*220mm	/	\$35.95 (Epistar chip)
HB-R-10W			Dimension: 66mm*66mm*65mm Watts: 10W CREE chip Lumen: 750LM Voltage: 10-30V DC CCT: 6500K Waterproof rate: IP67 Lens: toughened glass Casing color: black Casing metrial: Aluminum alloy Light distribution: focus15° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(32pcs/carton, gross weight: 25kg) Carton dimension: 445mm*253mm*188mm	\$14.55 (CREE chip)	/
HB-R-10W-C			Dimension: 54mm*65mm*100mm Watts: 10W CREE chip Lumen: 850LM Voltage: 10-30V DC CCT: 6500K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing metrial: Aluminum alloy Light distribution: focus15° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(12pcs/carton, gross weight: 18kg) Carton dimension: 480mm*320mm*400mm	\$15.75 (CREE chip)	/
HB-R-12W-A			Dimension: 86mm*76mm*112mm Watts: 12W (4PCS*3W LED Epistar high power chip) Voltage: 10-30V DC CCT: 6500K Lumen: 950LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing metrial: Aluminum alloy Light distribution: focus15° flood 60° Operating temperature-40°C-80°C Lifespan:30000 hours Package: 1pcs/package(20pcs/carton, gross weight: 10kg) Carton dimension: 480mm*280mm*220mm	/	\$14.65 (Epistar chip)
HB-R-12W-B			Dimension: 66mm*66mm*65mm Watts: 12 (4PCS*3W LED Epistar high power chip) Voltage: 10-30V DC Current: 12V/1A; 24V/0.5A Lumen: 950LM Waterproof rate: IP67 Lens: toughened glass Casing color: black Casing metrial: Aluminum alloy Light distribution: focus15° flood 60° Operating temperature-40°C-120°C Lifespan:30000 hours Package: 1pcs/package(32pcs/carton, gross weight: 20kg) Carton dimension: 445mm*253mm*188mm	/	\$14.65 (Epistar chip)
HB-R-18W			Dimension: 82mm*80mm*75mm Watts: 18W (6PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Lumen: 1150LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing metrial: diecast aluminum Operating temperature-40°C-80°C Lifespan:50000 hours Package: 1pcs/package(18pcs/carton, gross weight: 14kg) Carton dimension: 420mm*350mm*240mm	\$19.98 (CREE chip)	/





















HB-R-20W			Dimension: 82mm*80mm*75mm Watts: 20W (4PCS*5W CREE chip) Voltage: 10-30V DC CCT: 6000K Lumen: 1500LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: diecast aluminum Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package (18pcs/carton, gross weight: 14kg) Carton dimension: 420mm*350mm*240mm	\$19.98 (CREE chip)	/
HB-R-20W-B			Dimension: 93mm*93mm*70mm Watts: 20W CREE integrated chip Voltage: 10-60V DC CCT: 6500K Lumen: 1150LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Light distribution: focus 15° flood 60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 13.5kg) Carton dimension: 480mm*230mm*320mm	\$36.95 (CREE chip)	/
HB-R-25W			Dimension: 93mm*93mm*70mm Watts: 25W CREE integrated chip Voltage: 10-60V DC CCT: 6500K Lumen: 1150LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Light distribution: focus 15° flood 60° Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 13.5kg) Carton dimension: 480mm*230mm*320mm	\$42.99 (CREE chip)	/
HID POD		. Internal ballast . HID bulb: H3 . HID Power: 35W/55W . Operating Voltage: 12V/24V/9-36V . Luminous: 3200LM/4000LM/4850LM (±400lum) . Waterproof rate: IP67 . Working Temperature: -40°C~+80°C . Vibration: 20Grms 24-2000Hz . Optional Color: Black	. Color Temperature: 6000K. (4300K-12000K optional) . Material: Plastic . Optional Beam: Smooth spot, Striped flood . material :ABS	4 inch: 35W: \$24.75; 55W: \$26.95 7 inch: 35W: \$26.95; 55W: 29.25; 75W: \$37.95 9 inch: 35W: \$33.45; 55W: \$35.85; 75W: \$43.95	
HB-S-15W			Dimension: 145mm*45mm*70mm Watts: 15W (5PCS*3W LED Epistar high power chip) Voltage: 10-30V DC CCT: 6000K Lumen: 980LM Waterproof rate: IP67 Lens: PMMA Casing color: white/black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 10kg) Carton dimension: 400mm*200mm*200mm	\$16.98 (CREE chip)	\$13.98 (Epistar chip)
HB-S-18W			Dimension: 145mm*45mm*70mm Watts: 18W (6PCS*3W LED Epistar high power chip) Voltage: 10-30V DC CCT: 6000K Lumen: 1150LM Waterproof rate: IP67 Lens: PMMA Casing color: white/black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 10kg) Carton dimension: 500mm*440mm*220mm	\$18.35 (CREE chip)	\$14.55 (Epistar chip)
HB-S-9W			Dimension: 110mm*60mm*56mm Watts: 9W (3PCS*3W LED Epistar high power chip) Voltage: 10-30V DC CCT: 6000K Lumen: 880LM Waterproof rate: IP67 Lens: PMMA Casing color: white/black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 14kg) Carton dimension: 273mm*230mm*295mm	/	\$12.98 (Epistar chip)
HB-S-18W-B			Dimension: 110mm*60mm*56mm Watts: 18W (6PCS*3W LED Epistar high power chip) Voltage: 10-30V DC CCT: 6000K Lumen: 1250LM Waterproof rate: IP67 Lens: PMMA Casing color: white Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 17kg) Carton dimension: 273mm*230mm*295mm	/	\$13.98 (Epistar chip)
HB-S-20W			Dimension: 110mm*60mm*56mm Watts: 20W (2PCS*10W CREE chip) Voltage: 10-30V DC CCT: 6000K Lumen: 1900LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (20pcs/carton, gross weight: 14kg) Carton dimension: 273mm*230mm*295mm	\$24.98 (CREE chip)	/






















HB-S-33W			Dimension: 145mm*122mm*78mm Watts: 33W (11PCS*3W Epistar high power chip) Voltage: 10-30V DC CCT: 6000K Lumen: 2690LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (12pcs/carton, gross weight: 18.8kg) Carton dimension: 390mm*380mm*35mm	/	\$32.55 (Epistar chip)
HB-S-45W			Dimension: 145mm*122mm*78mm Watts: 45W (15PCS*3W Epistar high power chip) Voltage: 10-30V DC CCT: 6000K Lumen: 3900LM Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 30000 hours Package: 1pcs/package (12pcs/carton, gross weight: 18.8kg) Carton dimension: 390mm*380mm*35mm	/	\$32.95 (Epistar chip)
HB-CU-36W 7.5" dual row			LED power: 36W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 8.93A@12V, 4.46A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 20inch	\$44.95 (CREE chip)	\$38.35 (Epistar chip)
HB-CU-72W 13.5" dual row			LED power: 72W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 8.93A@12V, 4.46A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 20inch	\$72.55 (CREE chip)	\$62.35 (Epistar chip)
HB-CU-120W 21.5" dual row			LED power: 120W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 8.93A@12V, 4.46A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 20inch	\$129.45 (CREE chip)	\$115.35 (Epistar chip)
HB-CU-180W 31.5" dual row			LED power: 180W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 13.4A@12V, 6.7A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood/comb 30000 hours above life time Dimensions: 30inch	\$194.25 (CREE chip)	\$169.35 (Epistar chip)
HB-CU-240W 41.5" dual row			LED power: 240W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 17.85A@12V, 8.93A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 40inch	\$212.55 (CREE chip)	\$189.65 (Epistar chip)
HB-CU-288W 50" dual row			LED power: 288W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 21.42A@12V, 10.71A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 50inch	\$249.99 (CREE chip)	\$219.46 (Epistar chip)
HB-CUS-60W 20" single row		/	LED power: 60W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 4.26A@12V, 2.1A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 20inch	\$89.85 (CREE chip)	/
HB-CUS-100W 20" single row			LED power: 100W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 8.93A@12V, 4.46A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 20inch	\$129.95 (CREE chip)	/
HB-CUS-140W 30" single row			LED power: 140W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 13.4A@12V, 6.7A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood/comb 30000 hours above life time Dimensions: 30inch	\$173.25 (CREE chip)	



HB-CUS-200W 40" single row			LED power: 200W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 17.85A@12V, 8.93A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 40inch	\$245.55 (CREE chip)	
HB-CUS-240W 50" single row	hot 		LED power: 240W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 21.42A@12V, 10.71A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 50inch	\$289.55 (CREE chip)	
HB-L-36W 7.5" dual row	hot 		Dimension: 271.1mm*86.5mm*111.2mm Watts: 36W (12PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 320mm*180mm*150mm	\$32.65 (CREE chip)	\$27.55 (Epistar chip)
HB-L-72W 13.5" dual row	hot 		Dimension: 424.1mm*86.5mm*111.2mm Watts: 72W (24PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 480mm*180mm*150mm	\$53.98 (CREE chip)	\$45.95 (Epistar chip)
HB-L-72W 13.5" B dual row			Dimension: 424.1mm*86.5mm*111.2mm Watts: 72W (24PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 480mm*180mm*150mm	\$65.98 (CREE chip)	\$58.98 (Epistar chip)
HB-L-108W 20" dual row			Dimension: 569mm*125mm*90mm Watts: 108W (36PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 600mm*160mm*150mm	\$76.95 (CREE chip)	\$64.95 (Epistar chip)
HB-L-120W 21.5" dual row	hot 		Dimension: 628.1mm*86.5mm*111.2mm Watts: 120W (40PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Carton dimension: 680mm*180mm*150mm	\$86.95 (CREE chip)	\$74.95 (Epistar chip)
HB-L-120W 21.5" B dual row			Dimension: 628.1mm*86.5mm*111.2mm Watts: 120W (40PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Carton dimension: 680mm*180mm*150mm	\$86.95 (CREE chip)	\$79.95 (Epistar chip)
HB-L-180W 31.5" dual row	hot 		Dimension: 883.1mm*86.5mm*111.2mm Watts: 180W (60PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Carton dimension: 930mm*180mm*150mm	\$128.85 (CREE chip)	\$105.88 (Epistar chip)
HB-L-240W 41.5" dual row	hot 		Dimension: 1138.1mm*86.5mm*111.2mm Watts: 240W (80PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Carton dimension: 1190mm*180mm*150mm	\$167.55 (CREE chip)	\$149.5 (Epistar chip)
HB-L-288W 50" dual row	hot 		Dimension: 1343mm*86.5mm*111.2mm Watts: 288W (96PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing material: diecast aluminum housing Operating temperature: -40°C~80°C Lifespan: 30000 hours Beam: 8degree Spot/120degree flood/Combo Carton dimension: 1390mm*180mm*150mm	\$208.35 (CREE chip)	\$169.85 (Epistar chip)

HB-L-288W 50" B dual row			Dimension: 1343mm*86.5mm*111.2mm Watts: 288W (96PCS*3W CREE high power chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black/white Casing metrial:diecast aluminum housing Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Carton dimension: 1390mm*180mm*150mm	\$208.35 (CREE chip)	/
HB-L-60W 13.5" single row			Watts: 60W (6PCS*10W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 490mm*180mm*150mm	\$65.8 (CREE chip)	/
HB-L-100W 21.5" single row			Watts: 100W (10PCS*10W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 690mm*180mm*150mm	\$108.5 (CREE chip)	/
HB-L-140W 31.5" single row			Watts: 140W (14PCS*10W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 950mm*180mm*150mm	\$153.5 (CREE chip)	/
HB-L-200W 41.5" single row			Watts: 200W (20PCS*10W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 1200mm*180mm*150mm	\$204.8 (CREE chip)	/
HB-L-240W 50" single row			Watts: 240W (24PCS*10W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Material:Diecast aluminum housing Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 1400mm*180mm*150mm	\$245.00 (CREE chip)	/
HB-T-30W 10"			Watts: 30W (6PCS*5W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Material:Diecast aluminum housing Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 500mm*180mm*150mm	\$39.96 (CREE chip)	/
HB-T-60W 20"			Watts: 60W (12PCS*5W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Material:Diecast aluminum housing Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 7400mm*160mm*140mm	\$69.95 (CREE chip)	/
HB-T-90W 30"			Watts: 90W (18PCS*5W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Material:Diecast aluminum housing Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 980mm*160mm*140mm	\$99.98 (CREE chip)	/
HB-T-120W 40"			Watts: 120W (20PCS*5W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color:black/white Material:Diecast aluminum housing Mounting Bracket: Alu firm bracket Operating temperature-40°C~80°C Lifespan:30000 hours Beam: 8degree Spot/120degree flood/Combo Package dimension: 1220mm*160mm*140mm	\$132.8 (CREE chip)	/
HB-H-20W 5.5"			Dimension: 113mm*70mm*97mm Watts: 20W 2PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(10pcs/carton, gross weight: 11kg) Carton dimension:44*43*32cm	\$23.55 (CREE chip)	/

HB-H-40W 9.5"		Dimension: 203mm*70mm*97mm Watts: 20W 2PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(6pcs/carton, gross weight: 11kg) Carton dimension:43*31.5*32cm	\$32.98 (CREE chip)	/
HB-H-80W 17.5"		Dimension: 383mm*70mm*97mm Watts: 80W 8PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(6pcs/carton, gross weight: 16kg) Carton dimension:49.5*43*32cm	\$59.95 (CREE chip)	/
HB-H-120W 22.5"		Dimension:563mm*70mm*97mm Watts: 120W 12PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(4pcs/carton, gross weight: 15kg) Carton dimension:67.5*29*32cm	\$89.96 (CREE chip)	/
HB-H-160W 32.5"		Dimension:723mm*70mm*97mm Watts: 160W 16PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(4pcs/carton, gross weight: 18kg) Carton dimension:85.5*29*32cm	\$119.96 (CREE chip)	/
HB-H-200W 37"		Dimension:943mm*70mm*97mm Watts: 200W 20PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(4pcs/carton, gross weight: 27kg) Carton dimension:103*29*32cm	\$147.32 (CREE chip)	/
HB-H-240W 43.5"		Dimension: 1110mm*70mm*97mm Watts: 240W 24PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(4pcs/carton, gross weight: 27kg) Carton dimension:103*29*32cm	\$168.88 (CREE chip)	/
HB-H-260W 47"		Dimension: 1193mm*70mm*97mm Watts: 200W 20PCS*10W Voltage: 10-45V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum alloy Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood Package: 1pcs/package(4pcs/carton, gross weight: 30kg) Carton dimension:130.5*29*32cm	\$196.55 (CREE chip)	/
HB-C-18W 4"		 Dimension: 99*73*107mm Watts: 18W 6PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(40pcs/carton, gross weight: 25kg) Carton dimension:95*28*56 cm	\$17.45 (CREE chip)	/
HB-C-24W 5.5"		 Dimension: 137*89.6*72 mm Watts: 24W 8PCS*3W Flux: 19800lm Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(12pcs/carton, gross weight: 12.5kg) Carton dimension:45*28*34cm	\$24.65 (CREE chip)	/
HB-C-36W 7"		 Dimension: 167*73*107mm Watts: 36W 12PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing material: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(20pcs/carton, gross weight: 21kg) Carton dimension:85*26*27cm RED color LEDs version is \$38.99 per piece.	\$33.99 (CREE chip)	/

HB-C-36W 7" B			Dimension: 167*73*107mm Watts: 36W 12PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(20pcs/carton, gross weight: 21kg) Carton dimension:85*26*27cm	\$38.25 (CREE chip)	/
HB-C-48W 9.5"			Dimension: 239*89.6*72 mm Watts: 48W 16PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed	\$44.68 (CREE chip)	\$42.35 (Epistar chip)
HB-C-72W 12"			Dimension: 305*73*107mm Watts: 72W 24PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(4pcs/carton, gross weight: 7.5kg) Carton dimension:31*26*27 cm	\$56.85 (CREE chip)	\$49.25 (Epistar chip)
HB-C-108W 17"			Dimension: 438*73*107mm Watts: 108W 36PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(4pcs/carton, gross weight: 10kg) Carton dimension:45*26*27 cm	\$73.99 (CREE chip)	/
HB-C-120W 21.5"			Dimension: 545*89.6*72 mm Watts: 120W 40PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed	\$77.65 (CREE chip)	
HB-C-126W 20"			Dimension: 505*73*107mm Watts: 126W 42PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(4pcs/carton, gross weight: 12kg) Carton dimension:56*26*27 cm	\$93.40 (CREE chip)	/
HB-C-168W 30"			Dimension: 749*89.6*72 mm Watts: 168W 56PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed	\$112.68 (CREE chip)	\$99.00 (CREE chip)
HB-C-192W 33.5"			Dimension: 851*89.6*72mm Watts: 192W 64PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(3pcs/carton, gross weight: 15kg) Carton dimension: 94.2*38.8*23.8cm	\$121.50 (CREE chip)	\$109.45 (Epistar chip)
HB-C-240W 41"			Dimension: 1045*89.6*72 mm Watts: 240W 80PCS*3W Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PC Casing color: black Casing metrial: Aluminum Operating temperature-40°C~80°C Lifespan:30000 hours Beam: focus/flood/mixed Package: 1pcs/package(2pcs/carton, gross weight: 11.8kg) Carton dimension:115*26*24cm	\$159.28 (CREE chip)	\$129.44 (Epistar chip)
HB-M-48W			Dimension: 145*150.5*93 mm Luminous flux: 3820 lm Watts: 48W (16PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing metrial: Aluminum alloy Operating temperature-40°C~80°C Lifespan:50000 hours Package: 1pcs/package, 1.65kg/pcs Carton dimension: 47*44*30cm	\$49.95 (CREE chip)	\$46.60 (Epistar chip)

HB-M-72W			Dimension: 196*150.5*93 mm Luminous flux: 5980 lm Watts: 72W (24PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package, 2.5kg/pcs Carton dimension: 57.4*44*30cm	\$58.80 (CREE chip)	\$55.00 (Epistar chip)
HB-M-96W			Dimension: 247*150.5*93 mm Luminous flux: 7020 lm Watts: 96W (32PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package, 3.2kg/pcs Carton dimension: 34.3*44*30cm	\$69.80 (CREE chip)	\$65.50 (Epistar chip)
HB-M-120W			Dimension: 298*150.5*93 mm Luminous flux: 9090 lm Watts: 120W (40PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package,	\$84.55 (CREE chip)	79.55 (Epistar chip)
HB-M-144W			Dimension: 349*150.5*93 mm Luminous flux: 11080 lm Watts: 144W (48PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package,	\$99.35 (CREE chip)	96.35 (Epistar chip)
HB-M-168W			Dimension: 400*150.5*93 mm Luminous flux: 12700 lm Watts: 144W (48PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package, 4.15kg/pcs Carton dimension: 49.6*44*30cm	\$115.45 (CREE chip)	108.20 (Epistar chip)
HB-M-216W			Dimension: 502*150.5*93 mm Luminous flux: 16870 lm Watts: 216W (72PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package, 5kg/pcs Carton dimension: 59.8*44*30cm	\$139.85 (CREE chip)	129.95 (Epistar chip)
HB-M-288W			Dimension: 655*150.5*93 mm Luminous flux: 23100 lm Watts: 288W (96PCS*3W CREE chip) Voltage: 10-30V DC CCT: 6000K Waterproof rate: IP67 Lens: PMMA Casing color: black Casing material: Aluminum alloy Operating temperature: -40°C~80°C Lifespan: 50000 hours Package: 1pcs/package	\$188.95 (CREE chip)	174.50 (Epistar chip)
LED bar/pods harness		5 meters	for LED bars/single pod/dual pods	\$9.80	
	HB-R-10W	10W		Notes: 1. Above price is Ex-Harbor factory and valid for 3 months. Warranty is 1 year. 2. All the lights with neutral box package. If OEM pack, extra 300USD charged, and will be returned for single items value reach 5000USD. 3. OME service is available for large quantity and steady orders. 4. Payment: Paypal, T/T, western union are acceptable 5. Delivery time is with 5-7 business day after payment confirmed. 6. Defective products within warranty shipping cost should be paid by client side.	
	HB-R-20W	20W			
	HB-27W-A	27W			

	HB-C series	36W 72W 108W		
---	-------------	--------------------	---	--

Real show!!!

