

STAINLESS STEEL TRANSOM GANGWAY 6996



model	X (mm/inch)	Y (mm/inch)	K (mm/inch)	α	β	loading standard (kg/lbs)	weight (kg/lbs)
6996/25	2525 100"	1545 61"	350 14"	50°	40°	300/660	127/280
6996/27	2725 108"	1695 67"	400 16"	50°	40°	300/660	129/284
6996/30	2975 117"	1795 71"	400 16"	50°	40°	250/550	136/300
6996/33	3300 130"	1980 78"	400 16"	50°	40°	200/440	144/317
6996/36	3600 142"	2130 84"	400 16"	50°	40°	150/350	152/335

This gangway allows the boarding of 150 Kg / 330 lbs maximum (one person at a time).
IDEAL FOR JET SKI AND TENDER LIFTING.

X= maximum length of gangway when extended

Y= minimum length of gangway when retracted

K= the minimum distance to be maintained between the centre of rotation of the gangway and the centre of rotation of the ram (K).

α and β = the total angle the gangway can achieve.

The drawings have been studied considering a vertical transom. Variations of the transom angle and the different heights of dimension K will produce different values of angle α and β .

NEVER USE THE GANGWAY AS SPRINGBOARD. DIVING COULD CAUSE STRONG STRAINS THAT MIGHT DAMAGE THE GANGWAY AND ITS FASTENING ELEMENTS.

