



SIL-360 NX



HIGH EFFICIENCY PREMIUM MONO-PERC PV MODULE



CHUBB*

* Chubb provides error and omission insurance to Silfab Solar Inc.

INDUSTRY LEADING WARRANTY


All our products include an industry leading 25-year product workmanship and 30-year performance warranty.

40+ YEARS OF SOLAR INNOVATION

Leveraging over 40 years of worldwide experience in the solar industry, Silfab is dedicated to superior manufacturing processes and innovations such as Bifacial and Back Contact technologies, to ensure our partners have the latest in solar innovation.

NORTH AMERICAN QUALITY

Silfab is the leading automated solar module manufacturer in North America. Utilizing premium quality materials and strict quality control management to deliver the highest efficiency, premium quality PV modules.



■ BAA / ARRA COMPLIANT

These panels are designed and manufactured to meet Buy American Act Compliance. The US State Department, US Military and FAA have all utilized Silfab panels in their solar installations.

■ LIGHT AND DURABLE

Engineered to accommodate high wind load conditions for test loads validated up to 5400Pa uplift. The light-weight frame is exclusively designed for wide-ranging racking compatibility and durability.

■ QUALITY MATTERS

Total automation ensures strict quality controls during the entire manufacturing process at our ISO certified facilities.

■ DOMESTIC SUPPORT/SERVICES

Our 500+ North American team is ready to help our partners win the hearts and minds of customers, providing customer service and product delivery that is direct, efficient and local.

■ AESTHETICALLY PLEASING

All black sleek design, ideal for high-profile residential or commercial applications.

■ PID RESISTANT

PID Resistant due to advanced cell technology and material selection. In accordance to IEC 62804-1.

Electrical Specifications		SIL-360 NX mono PERC	
Test Conditions		STC	NOCT
Module Power (Pmax)	Wp	360	268
Maximum power voltage (Vpmax)	V	37.11	34.67
Maximum power current (Ipmax)	A	9.70	7.74
Open circuit voltage (Voc)	V	45.40	42.65
Short circuit current (Isc)	A	10.20	8.20
Module efficiency	%	19.7	18.3
Maximum system voltage (VDC)	V	1000	
Series fuse rating	A	20	
Power Tolerance	Wp	0 to +10	
Measurement conditions: STC 1000 W/m² • AM 1.5 • Temperature 25 °C • NOCT 800 W/m² • AM 1.5 • Measurement uncertainty ≤ 3% • Sun simulator calibration reference modules from Fraunhofer Institute. Electrical characteristics may vary by ±5% and power by 0 to +10W.			
Temperature Ratings		SIL-360 NX mono PERC	
Temperature Coefficient Isc		+0.064 %/°C	
Temperature Coefficient Voc		-0.28 %/°C	
Temperature Coefficient Pmax		-0.36 %/°C	
NOCT (± 2°C)		46 °C	
Operating temperature		-40/+85 °C	
Mechanical Properties and Components		SIL-360 NX mono PERC	
		Metric	Imperial
Module weight		20±0.2 kg	44±0.4 lbs
Dimensions (H x L x D)		1832 mm x 1000 mm x 38 mm	72.13 in x 39.4 in x 1.5 in
Maximum surface load (wind/snow)*		5400 Pa rear load / 5400 Pa front load	112.8/112.8 lb/ft²
Hail impact resistance		Ø 25 mm at 83 km/h	Ø 1 in at 51.6 mph
Cells		66 - Si mono-PERC - 5 busbar 158.75 x 158.75 mm	66 - Si mono-PERC - 5 busbar 6.25 x 6.25 in
Glass		3.2 mm high transmittance, tempered, DSM anti-reflective coating	0.126 in high transmittance, tempered, DSM anti-reflective coating
Cables and connectors (refer to installation manual)		1200 mm Ø 5.7 mm, MC4 from Staubli	47.2 in, Ø 0.22 (12AWG), MC4 from Staubli
Backsheet		High durability, superior hydrolysis and UV resistance, multi-layer dielectric film, fluorine-free PV backsheet	
Frame		Anodized Aluminum (Black)	
Bypass diodes		3 diodes-30SQ045T (45V max DC blocking voltage, 30A max forward rectified current)	
Junction Box		UL 3730 Certified, IEC 62790 Certified, IP67 rated	
Warranties		SIL-360 NX mono PERC	
Module product workmanship warranty		25 years**	
Linear power performance guarantee		30 years	
		≥ 97.1% end 1 st year	≥ 91.6% end 12 th year ≥ 85.1% end 25 th year ≥ 82.6% end 30 th year
Certifications		SIL-360 NX mono PERC	
Product		ULC ORD C1703, UL1703, CEC listed, UL 61215-1/-1-1/-2, UL 61730-1/-2, IEC 61215-1/-1-1/-2***, IEC 61730-1/-2***, CSA C22.2#61730-1/-2, IEC 62716	
Factory		Ammonia Corrosion; IEC61701:2011 Salt Mist Corrosion Certified, UL Fire Rating: Type 2 ISO9001:2015	



- Modules Per Pallet: 26
- Pallets Per Truck: 32
- Modules Per Truck: 832

*⚠ Warning. Read the Safety and Installation Manual for mounting specifications and before handling, installing and operating modules.

**12 year extendable to 25 years subject to registration and conditions outlined under "Warranty" at www.silfabsolar.com.

***Certification in progress.

PAN files generated from 3rd party performance data are available for download at: www.silfabsolar.com/downloads.



Silfab Solar Inc.
240 Courtneypark Drive East
Mississauga ON L5T 2Y3 Canada
Tel +1 905-255-2501 | Fax +1 905-696-0267
info@silfabsolar.com | www.silfabsolar.com

Silfab Solar Inc.
800 Cornwall Ave
Bellingham WA 98225 USA
Tel +1 360-569-4733

Silfab Solar Inc.
1770 Port Drive
Burlington WA 98233 USA
Tel +1 360-569-4733