

Winterize 2014	Completed	Notes	Tot Antifreeze		
Plumbing					
Winterize the toilet:		2 gals antifreeze	2		
Pump out the holding tank and add antifreeze		Run antifreeze through macerator			
Drain the water heater and put in bypass		Use shopvac to drain			
Empty freshwater tanks and add antifreeze		Pump antifreeze thru system	4		
protect pumps and hoses		4 gal antifreeze (pumped thru water tank)	4		
Clean shower sump		Add .5 gal antifreeze and run pump			
Winterize deck wash					
Close propane tank and Empty lines					
Antifreeze in Fridge Drain					
Deck					
Relocate Propane tanks from starboard side to port side					
Remove Bimini					
Service Windlas					
Vacum clean					
Remove all liquids and food					
Open lockers and drawers and hatches					
Varnish handrails					
Engine					
Flush engine raw-water circuit w/fresh water		4 gals or fresh water			
Flush engine raw-water circuit w/anti-freeze		5 gals of antifreeze	5		
Change engine oil & filter		14 qts 15/40 Rotella T heavy duty			
Change injector oil					
Check Transmission oil		.9 pts			
Replace Zincs					
check raw-water impeller					
Spray WD40 on unpainted parts					
Replace Racor fuel filters					
Cover air intake and exhaust					
Steering					
Oil cables					
Grease linkage					
Oil chains					
Remove and winterize OB					
Remove and winterize Generator					
Total pink antifreeze			15		